



产品采用标准 Product adoption standards

结构形式 structure type	双瓣旋启式止回阀 Dual-disc swing type check valve
设计标准 design standards	GB/T 12224
结构长度 Structure length	GB/T 15188.2
法兰连接 Flange connection	JB/T 79、GB/T9113、HB20592
试验和检验 Test and inspection	JB/T9092

注：阀门连接法兰及对焊端尺寸可根据用户要求设计制造

Note: The size of valve connecting flange and butt welding end can be designed and manufactured according to user requirements

主要零件材料 Material of main parts

序号No.	零件名称 Part name	材质 Material
1	阀体 Body	WCB、CF8、CF8M、CF8C、CF3、CF3M
2	阀瓣 Disc	WCB、CF8、CF8M、CF8C、CF3、CF3M
3	销轴 Pivot	1Cr13、2Cr13、1Cr18Ni9Ti、0Cr18Ni12Mo2Ti
4	弹簧 Spring	4Cr13、60Si2Mn、1Cr18Ni9Ti、0Cr18Ni12Mo2Ti

主要外形尺寸 Main dimensions

型号 Model:H76H、H76Y

PN (MPa)	DN (mm)	尺寸Dimensions(mm)		PN (MPa)	DN (mm)	尺寸Dimensions(mm)		PN (MPa)	DN (mm)	尺寸Dimensions(mm)	
		L	D			L	D			L	D
1.0	50	60	109	1.6	50	60	109	2.5	50	60	109
	65	67	129		65	67	129		65	67	129
	80	73	144		80	73	144		80	73	144
	100	73	164		100	73	164		100	73	164
	125	86	194		125	86	194		125	86	194
	150	98	220		150	98	220		150	98	220
	200	127	275		200	127	275		200	127	275
	250	146	330		250	146	332		250	146	332
	300	181	380		300	181	387		300	181	387
	350	184	440		350	184	447		350	184	447
	400	190	492		400	190	498		400	191	498
	450	203	542		450	203	558		450	203	558
500	219	597	500	219	620	500	219	620			
600	222	698	600	222	734	600	222	734			